



State of Ohio
Weatherization Program
Standards

Section

BASIC SAFETY STANDARDS

Subject

**Storage and Disposal
Requirements**

STORAGE AND DISPOSAL REQUIREMENTS 1406-1

Bagged materials shall be stacked by stepping back the layers and cross keying the bags at least every 10 bags high. **materials storage**
1406-1.1

Used lumber shall have all nails withdrawn before stacking. **lumber**
1406-1.2a

Lumber shall be stacked on level and solidly supported sills. **solidly supported**
1406-1.2b

Lumber shall be stacked to be stable and self supporting. **stable**
1406-1.2c

Lumber piles that are handled manually shall not be stacked more than sixteen feet high. **lumber piles**
1406-1.2d

All scrap lumber, waste material and rubbish shall be removed from the immediate work area, as the work progresses. **disposal**
1406-1.3

During the course of construction, alteration or repairs, form and scrap lumber with protruding nails and all other debris shall be kept cleared from work areas, passageways and stairs, in and around buildings or other structures. **clear work area**
1406-1.4

Disposal of waste material or debris by burning shall comply with local fire regulations and state regulations. **burning waste**
1406-1.5

Containers shall be provided for the collection of waste, trash, oily and used rags, and other refuse. Containers used for oily, flammable or hazardous wastes such as caustics, acids and harmful dusts shall be designed for such purposes and equipped with covers. **containers**
1406-1.6