

	<p style="text-align: center;">State of Ohio Weatherization Program Standards</p>	Section	PRIORITY LISTS
		Subject	Single Family and 2 - 4 Unit Buildings

Priority List for Single Family and Two to Four Unit Buildings

Standard Dwelling Type: A,B,C,D,E,F,G,I

Required Measures:

- Uniform Measures
 - Air leakage as determined by blower door testing.
 - Water heater insulation, always installed unless technical or safety reason exists.
 - Furnace tune-up as determined by required testing procedures using diagnostic equipment.
 - Duct insulation in non-conditioned areas.
 - Duct sealing.
 - Low flow shower head.
- Ceilings to <R-19 to R-38
- Uninsulated Walls to R-15
- Uninsulated Floors to R-19¹ and²

Optional Measures (NEAT Required, SIR of 1 or Greater):

- Partially Insulated Attics => R-19, Add to R-38
- Storm Windows Over Single Pane

¹Floors are only insulated if basement, crawlspace, or combination basement/crawl space separates a conditioned space from a non-conditioned space. If area is conditioned or unintentionally conditioned, this priority is not applicable. NEAT was done with Type U and was cost-effective.

²Perimeters are insulated in a conditioned basements, crawl spaces, or combinations if:

- a. Moisture can be controlled;
- b. Inhabitant activity suggests the insulation will stay in place undamaged; and
- c. the space can be cost-effectively air sealed from the exterior.

The perimeter surrounding unintentionally conditioned areas may be insulated, depending on the judgement of the inspector with input from the client as long as:

- a. Moisture can be controlled and the cost of floor insulation, along with the cost of the resulting required measures of pipe insulation and duct insulation, will exceed the cost of perimeter insulation; and
- b. The space can be cost-effectively air sealed from the exterior or interior.

Section 202-5 provides further clarification on footnotes 1 and 2.